



Heyco® Back-Up Washer For Strain Relief Bushings



PART NO.	DESCRIPTION	INSIDE DIAMETER		OUTSIDE DIAMETER		THICKNESS	
		in.	mm.	in.	mm.	in.	mm.
7592	SRW 500	.500	12,7	.625	15,9	.025	0,6

- Made of zinc-plated steel.
- Used together with our Strain Relief Bushings.
- For situations where the panel is too flexible to support UL's 35# strain relief pull-out test.
- OR for situations where the panel is thin relative to the strain relief's locking slot. The backup washer eliminates "play".
- OR can be used to contain the strain relief bushing in U-slot openings.

Heyco® Metal Strain Relief Bushings For Round Cables



WILL FIT THESE CABLES UL Type Description	Approximate Diameter		PART NO.	DESCRIPTION	PART DIMENSIONS						ATTACHING PLIERS NO.
	in.	mm.			O		W		L		
HPD	.312	7,9	7410	MSR-1	.296	7,5	.593	15,1	.171	4,4	0019
SJ	.300-.343	7,6-8,7	7411	MSR-1A	.203	5,2	.531	13,5	.171	4,4	0018
SV	.250	6,4	7412	MSR-1B	.296	7,5	.500	12,7	.171	4,4	0018
SJ	.380	9,6	7414	MSR-2W	.265	6,7	.781	19,8	.171	4,4	0018
HPD	.312	7,9	7418	MSR-2S	.295	7,5	.781	19,8	.171	4,4	0019
SJ	.300-.343	7,6-8,7	7419	MSR-2A	.203	5,2	.781	19,8	.171	4,4	0018
HPD	.312	7,9	7420	MSR-2	.296	7,5	.765	19,5	.171	4,4	0019
HPD	.312	7,9	7430	MSR-3	.296	7,5	.656	16,7	.171	4,4	0019

- Made of plated steel.
- Absorbs pull force only, to help meet UL and CSA requirements.
- Designed to be attached to wire and cable inside of the panel.
- Permanent grip, nonslip design.
- Easy assembly with recommended hand pliers.
- See page 3-25 for Assembly Tools.

