



# Heyco® Strain Relief Mounting Hole Plugs

Standardize Panel Design and Fill Unused Holes







- Closes unused strain relief mounting holes or Double "D" holes punched or molded with two opposing flats.
- Convex, matte finish head tapers to a thin edge.
- Locks firmly in panels up to .125" (3,2 mm) thick.
- Quick and easy installation.
- Use our rectangular plugs #1890 and #1892 to fill unneeded square Lockit™ Strain Relief mounting holes.

PANEL DIMENSIONS						PART NO.	DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		D Long Axis		C Short Axis				Black	A Head Diameter		B Overall Height
in.	mm.	in.	mm.	in.	mm.		in.	mm.	in.	mm.	
.125	3,2	.437	11,1	.390	9,9	<b>2488</b>	DD-437-390	.531	13,5	.406	10,3
.125	3,2	.500	12,7	.445	11,3	<b>2491</b>	DD-500-445	.578	14,7	.406	10,3
.125	3,2	.562	14,3	.530	13,5	<b>2494</b>	DD-562-530	.656	16,7	.406	10,3
.125	3,2	.625	15,9	.550	14,0	<b>2497</b>	DD-625-550	.728	18,5	.406	10,3
.125	3,2	.750	19,0	.625	15,9	<b>2503</b>	DD-750-625	.921	23,4	.406	10,3
.125	3,2	.875	22,2	.770	19,6	<b>2509</b>	DD-875-770	1.016	25,8	.453	11,5
.157	4,0	.690	17,5	.690	17,5	<b>1892</b>	RP-175-175	.830	21,1	.467	11,9
.099	2,5	.512	13,0	.453	11,5	<b>1890</b>	RP-115-130*	.580	14,7	.403	10,2

Standard color black. Consult Heyco for white and other colors.

\*Rectangular plug to fill unneeded Lockit Strain Relief Mounting holes/not UL or CSA.

Locking finger steps designed in fractional increments.



1890

Quick Specs

Material	6/6 Nylon
Certifications	Recognized under the Component Program of Underwriters' Laboratories File E15331 Certified by the Canadian Standards Association File LR8919
Flammability Rating	94V-2
Material Temperature Index	257°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)